

PCT/US 00/05200

10/09735

REC'D 02 MAY 2000

WIPO PCT

EJKU

PA 203243

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

February 11, 2000

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/122,418

FILING DATE: March 02, 1999

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)



By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS

L. Edelen

L. EDELEN
Certifying Officer

"Express Mail" mailing label number EH267761225US

Date of Deposit March 2, 1999

I hereby certify that this paper/fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231

Steven R. Chuey 39,140
Agency mailing application Reg No

Signature of Attorney mailing application

PTO/SB/16 (6-95)
Approved for use through 04/11/98. OMB 0651-0037
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL PATENT APPLICATION under 37 CFR §1.53(b)(2).

Docket Number		7450P		Type a plus sign (+) inside this box ⇒		+	
INVENTOR(s) / APPLICANT(s)							
LAST NAME	FIRST NAME	MIDDLE INITIAL	RESIDENCE (CITY AND EITHER STATE OR FOREIGN COUNTRY)				
VanHauwermeiren	Tim	(nmn)	Brussels, Belgium				
Bettiol	Jean-Luc	P.	Brussels, Belgium				
Bouvette	Mariane	(nmn)	Brussels, Belgium				
Dewaele	Joost	(nmn)	Brussels, Belgium				
Pasin	Merih	(nmn)	Brussels, Belgium				
Vos	Eddy	(nmn)	Brussels, Belgium				
TITLE OF THE INVENTION (280 characters max)							
Method For Cleaning And Refreshing Fabrics							
CORRESPONDENCE ADDRESS							
Steven R. Chuey The Procter & Gamble Company Ivorydale Technical Center 5299 Spring Grove Avenue Cincinnati							
STATE	Ohio	ZIP CODE	45217	COUNTRY	USA		
ENCLOSED APPLICATION PARTS (check all that apply)							
<input checked="" type="checkbox"/>	Specification	Number of Pages: 19	+ Abstract	<input type="checkbox"/> Small Entity Statement			
<input type="checkbox"/>	Drawing(s)	Number of Sheets: _	<input type="checkbox"/> Other (specify) _				
METHOD OF PAYMENT (check one)							
<input type="checkbox"/>	A check or money order is enclosed to cover the Provisional filing fees			PROVISIONAL FILING FEE AMOUNT(S)	\$150.00		
<input checked="" type="checkbox"/>	The Commissioner is hereby authorized to charge filing fees specified under 37 CFR §1.19(f) and credit Deposit Account Number: 16-2480						

The invention was made by an agency of the United States Government or under a contract with an agency of United States Government.

☒ No

☐ Yes, the name of the U. S. Government agency and the Government contract number are: _____

Respectfully submitted,

SIGNATURE

Date 3/2/99

TYPED or PRINTED NAME Steven R. Chuey REGISTRATION NO. 39,140
(if appropriate)

☐ Additional inventors are being named on separately numbered sheets attached hereto

PROVISIONAL PATENT APPLICATION FILING ONLY

Burden Hour Statement: This form is estimated to take .2 hours to complete. Time will vary depending upon the needs of the individual cases. Any comments on the amount of time you are required to complete this form should be sent to the Office of Assistance Quality and Enhancement Division, Patent and Trademark Office, Washington, DC 20231, and to the Office of Information and Regulatory Affairs, Office of Management and Budget (Project 0651-0037), Washington, DC 20503. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Patent Application; Assistant Commissioner for Patents, Washington, D.C. 20231.

METHOD FOR CLEANING AND REFRESHING FABRICS

5

Tim Van Hauwermeiren

Jean-Luc P. Bettiol

Mariane Bouvette

Joost Dewaele

Merih Pasin

10

Eddy Vos

TECHNICAL FIELD

The present invention relates to methods useful for cleaning and refreshing fabrics in a non-immersion cleaning process. Temperature and relative humidity are controlled in the multi-step processes of this invention.

BACKGROUND OF THE INVENTION

Certain delicate fabrics are not suitable for conventional in-home immersion cleaning processes. Home washing machines, which provide excellent cleaning results for the majority of fabrics used in today's society, can, under certain conditions, shrink or otherwise damage silk, linen, wool and other delicate fabrics. Consumers typically have their delicate fabric items "dry-cleaned". Unfortunately, dry-cleaning usually involves immersing the fabrics in various hydrocarbon and halocarbon solvents that require special handling and the solvent must be reclaimed, making the process unsuitable for in-home use. Hence, dry-cleaning has traditionally been restricted to commercial establishments making it less convenient and more costly than in-home laundering processes.

Attempts have been made to provide in-home dry-cleaning systems that combine the fabric cleaning and refreshing of in-home, immersion laundering processes with the fabric care benefits of dry-cleaning processes. One such in-home system for cleaning and refreshing garments comprises a substrate sheet containing various liquid or gelled cleaning agents, and a plastic bag. The garments are placed in the bag together with the sheet, and then tumbled in a conventional clothes dryer. In a current commercial embodiment, multiple single-use flat sheets comprising a cleaning/refreshing agent and a single multi-use plastic bag are provided in a package.

60122418-030299

Unfortunately, these prior processes often involved only one step with regards to temperature and relative humidity. That is, the tumble dryer was set for a particular temperature and time. The humidity in the bag was a function of the moisture loaded in the bag and the temperature setting. But once the time and temperature were selected, the one
5 step process was set. Moreover, when using a conventional tumble dryer, the consumer is often limited to the manufacturer's pre-set temperature conditions, which are established for drying clothes, not for cleaning and refreshing them. Often these manufacturer's conditions are sub-optimal with respect to one or more of dewrinkling, deodorizing, and perfume deposition.

10 Moreover, such in-home processes are designed for use in a conventional clothes dryer, or the like apparatus. Such apparatuses are not always readily available, they are often uneconomical, and in many countries clothes dryers are simply unnecessary. For example, in many warm tropical regions people do not typically own clothes dryers because their clothes can be dried year-round by hanging them outside in the sun. In the areas of the
15 world where people do not typically own clothes dryers, products that require a heating apparatus, such as a clothes dryer, are of little or no value.

Steamer cabinets have also been utilized in the to treat fabric articles with heavy doses of steam. Unfortunately, these high temperature, high relative humidity processes can have negative effects on fabric articles. In addition to the harsh effect on fabrics, a drying
20 step is often required that puts even further strain on the fabrics. The drying step also requires additional time and energy, and often results in undesirable shrinkage. And finally, steamer cabinets are typically wasteful with respect to steam because it is only water.

Thus, there is a need to develop a domestic, non-immersion cleaning and refreshing process, and cleaning and refreshing compositions for use therein, which provides
25 acceptable cleaning without the need for a tumble dryer.

It has now also been unexpectedly discovered that by regulating temperature and relative humidity within a container during a domestic, non-immersion cleaning and refreshment process, dry clean only fabrics are cleaned, dewrinkled and refreshed. The present invention provides such methods for cleaning and refreshing fabrics.
30

SUMMARY OF THE INVENTION

In one aspect of the present invention there is provided a method for treating a fabric article comprising the steps of: a) placing the fabric article in a container having an opening and at least one wall that defines an interior void space; b) raising the temperature

and relative humidity of the air within the interior void space of the container to a predetermined first temperature and a predetermined first relative humidity for a predetermined first period of time; and c) changing at least one of the temperature or the relative humidity of the air within the interior void space of the container at the end of the first period of time to a predetermined second temperature and a predetermined second relative humidity for a predetermined second period of time.

In a preferred aspect of this invention vapor is used to raise the temperature and relative humidity of the air within the interior void space of the container, and more preferably the vent remains open at all times. In another aspect of this invention the vapor introduced into the interior void space of the container comprises water and a perfume.

In yet another aspect of the present invention there is provided a method for treating a fabric article comprising the steps of: a) placing the fabric article in a container having an opening and at least one wall that defines an interior void space; b) introducing ozone into the interior void space for a predetermined first period of time; and c) changing at least one of the temperature or the relative humidity of the air within the interior void space of the container at the end of the first period of time to a predetermined second temperature and a predetermined second humidity for a predetermined second period of time. The ozone can be generated by an ozone source, such as an ultraviolet lamp, within the interior void space of the container.

The present invention provides benefits over the prior art by defining the optimal process steps for cleaning and refreshing delicate fabric articles in an in-home non-immersion cleaning process. The methods of this invention can be carried out in any appropriate container, such as a plastic bag, a wardrobe, a cabinet, or a tumble dryer.

Unlike many prior processes, the methods of this invention involve at least two distinct steps, and preferably three steps. It has been surprisingly found that the optimal conditions for deodorizing a fabric article differ from the conditions that are best for dewrinkling. Likewise, perfume deposition onto a fabric article requires a third set of conditions for optimal performance. In the multi-step processes of this invention temperature, relative humidity or both can be manipulated and controlled. Alternatively, one step of the process can involve the introduction of ozone into the container to neutralize odor causing chemicals on the fabric articles being cleaned and refreshed.

Further the present invention provides a method of delivering an active ingredient, for example, perfume, to the fabrics being treated. Simultaneously, the methods herein minimize the amount of vapor delivered so that the actives are not wasted. And finally, the

60122418 030209

methods herein are designed to deliver only enough vapor to accomplish the fabric treatment process, without the need for additional mechanical drying.

DETAILED DESCRIPTION OF THE INVENTION

5 The present invention provides methods for cleaning and refreshing fabric articles in a domestic, non-immersion process. The methods require at least two steps, and preferably three. The methods can be carried out in any appropriate apparatus wherein temperature and relative humidity can be manipulated and controlled. In another aspect of this invention, one of the method steps involves the introduction of ozone into the container
10 to neutralize odor causing chemicals on the fabric articles being cleaned and refreshed.

A warm, humid environment inside the container volatilizes malodor components in the manner of a "steam distillation" process, and moistens fabrics and the soils thereon. This moistening of fabrics can loosen pre-set wrinkles, and because the fabric articles are hung in the container new wrinkles do not form. Proper selection of the amount of the
15 vapor, and specifically the amount of water used in the process and, importantly, proper venting of the container in the present manner can minimize shrinkage of the fabrics. Moreover, if the container is not vented, the volatilized malodorous materials removed from the fabrics can undesirably be re-deposited thereon.

Relative humidity is a well known concept to those in the fabric care arts. As used
20 herein, "relative humidity" means the ratio of the actual amount of water vapor in the air to the greatest amount possible at the same temperature.

Temperature and relative humidity controllers are well known to those skilled in the art, as are passive and active controllers. As used herein, an "active" controller is a controller that reads an input and supplies feedback to the device being controlled and that
25 device adjusts based on the feedback received. A "passive" controller, as used herein, is a controller that turns a device on or off, or opens or closes a device, based on a predetermined setting such as time. For example, a passive temperature controller would turn on a heating element or close a vent to increase the temperature in a given environment and after a certain period of time the heating element is turned off or the vent is opened. In
30 contrast, an active temperature controller reads the temperature and if, for example, the temperature is too low, the power to the heating element is increased or the vent is closed to increase the temperature.

60122418-030299

Method

To properly clean and refresh a fabric article, one must address many aspects of the article's appearance. Specifically, the fabric article should at least be substantially free of odor and wrinkles after a cleaning and refreshing operation. It is often preferred that the article be perfumed to give it a pleasant odor, and it should be free of localized stains. The methods of this invention require at least two steps designed toward deodorizing, dewrinkling and/or perfume deposition on a fabric article. Additionally, a manual spot removal process for removing localized stains is provided, but the spot removal process is conducted outside of the apparatus. The conditions for each of these methods steps are described in greater detail below.

While the method steps of this invention can be carried out in any appropriate order, the deodorization step will be discussed first. Deodorization must be distinguished from odor-masking, which involves applying a pleasant scent to a fabric to mask, or cover up the odors on the fabric. Deodorization, as used herein, involves the actual removal or neutralization of malodor causing chemicals. When the malodor causing constituents are removed or neutralized, the fabric article should have little or no residual odor. This step of the process can be carried out with ozone, which neutralizes odors, or with high temperatures and venting which removes the odor causing constituents.

The deodorization step, is described herein as the first step as a matter of convenience. It is understood that the deodorization and dewrinkling steps can be carried out in any order. If a perfume deposition step is employed, it necessarily should follow the deodorization step, so that the perfume is not stripped off of the fabric immediately after it is laid down.

Thus, when deodorization is the first step, the first temperature should be at least about 45°C, preferably at least about 60°C, and most preferably at least about 70°C and the first relative humidity should be least about 20%. At these relatively high temperatures, odor causing chemicals are stripped off of fabrics, and then preferably removed from the container via the vent. Even more preferably, the vent comprises a filter so that the odorous emanations do not enter the environment outside of the container. When the first temperature and first relative humidity are reached, the process time, that is, the first time, can be from about 2 minutes to about 20 minutes, preferably from about 5 minutes to about 15 minutes, and even more preferably from about 8 minutes to about 12 minutes.

The deodorization step described above can be supplemented, or even replaced by treating the fabric articles with ozone. The use of ozone to neutralize odors causing

662080-8742709

chemicals and to sanitize garments, for example, medical gowns, is well known to the art. Specifically see, published patent applications DE 24 33 909 and FR 2059 841, both of which are incorporated herein by reference. For purposes of the methods disclosed herein, ozone can be introduced into the container from any appropriate source, such as an ultraviolet lamp. One or more ozone sources can be used and they can be placed in any convenient place in, or adjacent the exterior of the container. The ozone source must be sized according to the volume of the container with consideration for the surface area of the fabric articles being cleaned and refreshed. Those skilled in the art will know what type and size of equipment to use for a given container.

10 The second step of the present invention is directed to dewrinkling, which requires relatively high temperature and relative humidity. Good air circulation is beneficial to the dewrinkling step, but not necessary. For the second step, i.e. the dewrinkling step, the second temperature should be greater than "T" as defined by the equation: $T = 60 - (0.17 * RH_2)$, wherein RH_2 is the second relative humidity in percent. RH_2 is preferably at least about 85%, and even more preferably at least about 90%. Preferably, the second temperature is less than about 90°C, more preferably less than about 80°C, and most preferably less than about 70°C. When the second temperature and second relative humidity are reached, the process time, that is, the second time, can be from about 2 minutes to about 20 minutes, preferably from about 5 minutes to about 15 minutes, and even more preferably from about 8 minutes to about 12 minutes.

20 Finally, there is preferably a third step which involves a gradual cool down of the interior void space. As the temperature decrease, the amount of vapor that the air can remain in the air decreases, and when the air becomes saturated the vapors begin to condense. Naturally, vapors will condense on the fabric articles on the inside of the bag, and as these articles dry, the active ingredients, such as perfume, remain behind. As discussed briefly above, the methods steps of this invention are designed to deliver actives without undue waste and without saturating the fabrics to the point where they need additional drying. Preferably, during the third step in the process the temperature within the interior void space decreases to a third temperature wherein the third temperature is less than about 45°C, preferably less than about 40°C, and more preferably less than about 35°C. This third step can last for a third period of time, which can be from about 2 minutes to about 20 minutes, preferably from about 3 minutes to about 10 minutes, and even more preferably from about 3 minutes to about 5 minutes.

As discussed in greater detail below, the vapor inside the container is preferably a cleaning and refreshment composition. The cleaning refreshment composition can be added to the container directly, via a sheet/substrate, in a cartridge or any other means that will be known to those skilled in the art. Preferably, the cleaning and refreshment composition is in a cartridge that is introduced into the interior void space of the container and the cleaning and refreshment composition is released from the cartridge into the interior void space of the container.

Apparatus

10 The methods of this invention can be conducted in any appropriate apparatus. Such apparatuses require a container that substantially encloses the fabric articles being cleaned and refreshed. By "substantially encloses", it is meant that the fabric articles are enclosed in the container, but that the container can, and preferably will, include one or more vents. The container must have an opening to access the fabric articles, and preferably, there is a
15 bar, hook or other device on which to hang the fabric articles.

The container preferably has only one wall configured like an egg shell. It has been found that the vapor, and subsequently the active ingredients, preferentially condense in the corners and along the sharp edges of a more conventional rectangular shaped cabinet. This is not to say that the methods of this invention cannot be conducted in rectangular cabinets;
20 they can. But the fewer sharp edges and corners the cabinet has, the more efficient it is. Thus, cabinets, wardrobes, and garment bags are all appropriate for use in the present invention. Moreover, a common tumble dryer may be an appropriate container, but these apparatuses do not normally have humidity controllers, nor do they have the ability to program a multi-step process with respect to both temperature and humidity. Thus, with
25 some additional programming and controllers, a common tumble dryer could be used for the methods of this invention.

In addition to the at least one wall that defines an interior void space, the containers of this invention preferably comprise: a vent; an active temperature controller capable of changing and maintaining the air temperature within the interior void space of the
30 container; a passive humidity controller capable of changing and maintaining the relative humidity of the air within the interior void space of the container; a heating element, which is capable of heating liquids to produce vapors and which can run dry to heat air; and an air circulation device, for example, a fan. Even more preferably, the air circulation device is a fan and the fan inlet is within the interior void space of the container so that at least a

60122418-030299

portion of the air within the void space of the container is recirculated. Also, there is preferably provided a filter in, or adjacent the exterior of the container

The water and actives, that is, the "cleaning and refreshment composition" can be added to the container in any appropriate way. The composition can be poured into the bag, poured into a reservoir that feeds into the heating element/humidifier, canisters can be used to inject the composition, or an absorbent substrate saturated with the composition can be placed in the bag. Substrates and compositions suitable for use in the methods of this invention are described in greater detail below. It is understood that those skilled in the art will know of other methods of adding actives to the container and those methods are within the scope of this invention.

Cleaning/Refreshment Composition

The cleaning/refreshment composition preferably comprises water and a member selected from the group consisting of surfactants, perfumes, preservatives, bleaches, auxiliary cleaning agents, shrinkage reducing compositions, organic solvents and mixtures thereof. The preferred organic solvents are glycol ethers, specifically, methoxy propoxy propanol, ethoxy propoxy propanol, propoxy propoxy propanol, butoxy propoxy propanol, butoxy propanol, ethanol, isopropanol and mixtures thereof. Fabric shrinkage reducing compositions that are suitable for use in the present invention are selected from the group consisting of ethylene glycol, all isomers of propanediol, butanediol, pentanediol, hexanediol and mixtures thereof. More preferably, the fabric shrinkage reducing compositions are selected from the group consisting of neopentyl glycol, polyethylene glycol, 1,2-propanediol, 1,3-butanediol, 1-octanol and mixtures thereof. The surfactant is preferably a nonionic surfactant, such as an ethoxylated alcohol or ethoxylated alkyl phenol, and is present at up to about 2%, by weight of the cleaning/refreshment composition. Typical fabric cleaning/refreshment compositions herein can comprise at least about 80%, by weight, water, preferably at least about 90%, and more preferably at least about 95% water.

The Examples below give specific ranges for the individual components of preferred cleaning/refreshment compositions for use herein. A more detailed description of the individual components of the cleaning/refreshment compositions, that is, the organic solvents, surfactants, perfumes, preservatives, bleaches and auxiliary cleaning agents can be found in U.S. Patent No. 5,789,368, which issued on August 4, 1998 to You et al. The entire disclosure of the You et al. patent is incorporated herein by reference. Additionally,

cleaning/refreshment compositions are described in co-pending U.S. Patent Application No. 08/789,171, which was filed on January 24, 1997, in the name of Trinh et al. The entire disclosure of the Trinh et al. Application is incorporated herein by reference. And shrinkage reducing compositions for use in this invention can be found in co-pending U.S. Provisional Application No. 60/097,596, entitled "Cleaning Compositions that Reduce Fabric Shrinkage", which was filed by Strang and Siklosi, on August, 24, 1998. The entire disclosure of the Strang and Siklosi application is incorporated herein by reference.

Substrate

10 In one embodiment of this invention the cleaning/refreshment composition can be releasably absorbed in an absorbent substrate, herein after referred to as a "substrate". The substrate releasably contains the composition. By "releasably contains" means that the composition is effectively released from the substrate onto the soiled fabrics as part of the cleaning and fabric refreshment processes herein. This release occurs mainly by
15 volatilization of the composition due to the heat from the supplemental heat source.

The substrate can be in any desired form, such as powders, flakes, shreds, and the like. However, it is highly preferred that the substrate be in the form of an integral pad or "sheet" that substantially maintains its structural integrity throughout the process. The substrates and sheets of this invention are sometimes referred to in the literature as
20 "carriers" or "absorbent carrier sheets"; it is understood that all of these labels refer to liquid absorbing materials that can be used to conveniently transport liquids. Such substrates are described in detail in U.S. Patent No. 5,789,368, to You et al. which was incorporated herein by reference above. The manufacture of these sheets forms no part of this invention and is already disclosed in the literature. See, for example, U.S. Patents 5,009,747,
25 Viazmensky, et al., April 23, 1991 and 5,292,581, Viazmensky, et al., March 8, 1994, which are incorporated herein by reference.

The substrate is intended to contain a sufficient amount of the cleaning/refreshment composition to be effective for the intended purpose. The capacity of the substrate for such a composition will vary according to the intended usage. The size of the substrate should
30 not be so large as to be unhandy for the user. Typically, the dimensions of the substrate will be sufficient to provide a macroscopic surface area (both sides of the substrate) of at least about 360 cm², preferably in the range from about 360 cm² to about 3000 cm². For example, a generally rectangular substrate may have the dimensions (X-direction) of from about 10 cm to about 35 cm, and (Y-direction) of from about 18 cm to about 45 cm.

In one preferred embodiment of this invention, the substrate is either a dark material, or is covered with a dark material, such as a black fabric. It is well known that dark materials absorb heat better than whiter materials. Thus, a dark substrate would tend to absorb more heat and volatilize more cleaning and refreshing composition if, for example, solar radiation is used as the supplemental heat source.

As discussed, the substrate can optionally be covered with a fibrous, preferably heat resistant and, most preferably, hydrophobic, coversheet as described in detail in U.S. Patent No. 5,789,368, to You et al. which was incorporated herein by reference above. Additionally, co-pending U.S. provisional application 60/077,556, which was filed on March 11, 1998, in the name of Wise et al., describes certain improvements to the coversheets of this invention. The entire disclosure of the Wise et al. application is incorporated herein by reference. Suitable combinations of the coversheets described in You et al. with the improvements described in Wise et al. can be employed, according to the desires of the manufacturer, without departing from the spirit and scope of the invention.

Spot Cleaning Composition

The user of the present process can be provided with various spot cleaning compositions to use in the optional pre-spotting procedure of this invention. These compositions are used to remove localized stains from the fabrics being treated, either before or after the cleaning and refreshing process defined herein. Necessarily, the spot cleaning composition must be compatible with the fabric being treated. That is, no meaningful amount of dye should be removed from the fabric during the spot treatment and the spot cleaning composition should leave no visible stains on the fabric. Therefore, in a preferred aspect of this invention there are provided spot cleaning compositions which are substantially free of materials that leave visible residues on the treated fabrics. This necessarily means that the preferred compositions are formulated to contain the highest level of volatile materials possible, preferably water, typically about 95%, preferably about 97.7%, and surfactant at levels of about 0.1% to about 0.7%. A preferred spot cleaning composition will also contain a cleaning solvent such as butoxy propoxy propanol (BPP) at a low, but effective, level, typically about 1% to about 4%, preferably about 2%.

Preferred spot cleaning methods and compositions are described in U.S. Patent No. 5,789,368, to You et al. which was incorporated herein by reference above. Additionally, spot cleaning methods and compositions are described in U.S. Patent No. 5,630,847, which

6012418-030299

issued on May 20, 1997, to Roetker. The entire disclosure of the Roetker patent is incorporated herein by reference.

Treatment Member

5 In one embodiment, a treatment member is provided to assist in removing localized stains from fabrics. In a preferred aspect of this invention, the spot cleaning composition is provided in a dispenser, such as a bottle, and the dispenser has a distal tip that can serve as the treatment member. Additionally, the treatment member can comprise an absorbent base material which can be, for example, a natural or synthetic sponge, an absorbent cellulosic
10 sheet or pad, or the like. In contact with and extending outward from this base material can be multiple protrusions. Specific examples of treatment members can be found in U.S. Patent No. 5,789,368, to You et al. which was incorporated herein by reference above.

Absorbent Stain Receiving Article

15 An absorbent stain receiving article, sometimes referred to herein as a stain receiver, can optionally be used in the optional pre-spotting operations herein. Such stain receivers can be any absorbent material which imbibes the liquid composition used in the pre-spotting operation. Disposable paper towels, cloth towels such as BOUNTY™ brand towels, clean rags, etc., can be used. However, in a preferred mode the stain receiver is
20 designed specifically to "wick" or "draw" the liquid compositions away from the stained area. One preferred type of stain receiver consists of a nonwoven pad, such as a thermally bonded air laid fabric ("TBAL"). Another highly preferred type of stain receiver for use herein comprises polymeric foam, wherein the polymeric foam comprises a polymerized water-in-oil emulsion, sometimes referred to as "poly-HIPE". The manufacture of
25 polymeric foam is very extensively described in the patent literature; see, for example: U.S. Patent No. 5,260,345 to DesMarais, Stone, Thompson, Young, LaVon and Dyer, issued November 9, 1993; U.S. Patent No. 5,550,167 to DesMarais, issued August 27, 1996, and U.S. 5,650,222 to DesMarais et al., issued July 22, 1997, all incorporated herein by reference. Typical conditions for forming the polymeric foams of the present invention
30 are described in co-pending U.S. Patent Application Serial No. 09/042,418, filed March 13, 1998 by T. A. DesMarais, et al., titled "Absorbent Materials for Distributing Aqueous Liquids", the disclosure of which is incorporated herein by reference. Additional disclosure of conditions for forming the polymeric foams for use in the present invention are described in co-pending U.S. Provisional Patent Application Serial No. 60/077,955, filed

66260-8742709

March 13, 1998 by T. A. DesMarais, et al., titled "Abrasion Resistant Polymeric Foam And Stain Receivers Made Therefrom", the disclosure of which is incorporated herein by reference.

5 The various stain receivers described herein, and described in the references incorporated herein by reference, preferably comprise a liquid impermeable backsheet. The backsheet can be made of, for example, a thin layer of polypropylene, polyethylene and the like. The backsheet provides protection for the surface that the stain receiver rests on from the spot cleaning composition. For example, spot cleaning processes are typically performed on a hard surface, such as a table top. The stain receiver is placed on the table and the fabric to be treated is placed on the stain receiver. Spot cleaning composition is applied to the stained area of the fabric and then drawn into the stain receiver. But in the absence of a back sheet, the spot cleaning composition can leak onto the table top, possibly causing damage thereto.

10 The following Examples further illustrate the invention, but are not intended to be limiting thereof.

EXAMPLE I

60122418.030299
Two extra-large men's jackets that have been exposed to cigarette smoke and wrinkled using standardized methods, are placed on clothes hangers. These jackets are then hung on the inside of a plastic bag that has two co-planer flat ends (the top and bottom) with the side walls being cylindrical and slightly outwardly bowed near the center. For illustration purposes only, the bag can be thought of as shaped like an egg shell with the top and bottom cut off. The container has a door for accessing the interior, and the door is closed with a zipper. A small slit near the bottom of the bag serves as the vent and the vent remains open at all times during this process.

25 On the interior of the bag is a fan, a heating element, a thermocouple and a reservoir that is in fluid communication with the heating element. Approximately 100 to 125 mls of a composition comprising approximately 99% water and 1% perfume, by weight, is poured into the reservoir and the door is closed.

30 An exterior "on/off" switch is turned on to begin the fabric refreshment process. The switch is connected to a programmable microprocessor that controls the multi-step process. First, the temperature is raised to about 70°C with a relative humidity of about 50%. This is accomplished by running the fan and the heating element, with little or no cleaning and refreshment composition in contact with the heating element. This first step

5 Finally, with the fan running the heating element is turned off and the interior of the bag cools naturally to about 45°C in less than about 10 minutes. The fan is turned off automatically, and an indicator light signals that the process is complete. The jackets are removed and they are substantially wrinkle free, deodorized and ready to wear.

10

15

20

25

30

automatically, and an indicator light signals that the process is complete. The jackets are removed and they are substantially wrinkle free, deodorized and ready to wear.

EXAMPLE III

5 Cleaning and Refreshing Compositions

While the cleaning and refreshment compositions of this invention can comprise water and perfume only, additional fabric treatment components can also be included. For example, fabric cleaning/refreshment compositions according to the present invention, for use in the methods described herein, are prepared as follows:

10	<u>Ingredient</u>	<u>% (wt.)</u>	
		<u>Sheet</u>	<u>Cartridge</u>
	Emulsifier (TWEEN 20)*	0.5	0
	Perfume	0.5	0.5
	KATHON®	0.0003	0
15	Sodium Benzoate	0.1	0
	Water	Balance	Balance
*Polyoxyethylene (20) sorbitan monolaurate available from ICI Surfactants.			

Additionally, preferred compositions for use in the methods of this invention are as

20 follows.

25	<u>Ingredient</u>	<u>% (wt.)</u>	<u>Range (% wt.)</u>
	Water	99.0	95.1-99.9
	Perfume	0.5	0.05-1.5
	Surfactant*	0.5	0.05-2.0
25	Ethanol or Isopropanol	0	Optional to 4%
	Solvent (e.g. BPP)	0	Optional to 4%
	Hydrogen peroxide	0	Optional to 4%
pH range from about 6 to about 8.			

EXAMPLE IV

30

Spot Cleaning Compositions

A spot cleaning composition for use in the present invention, preferably with a dispenser as defined above, and with a TBAL or poly-HIPE foam stain receiver, is prepared as follows:

<u>INGREDIENT</u>	<u>Anionic Composition (%)</u>
Hydrogen peroxide	1.000
Amino tris(methylene phosphonic acid)*	0.0400
Butoxypropoxypropanol (BPP)	2.000
5 NH ₄ Coconut E ₁ S	0.285
Dodecyldimethylamine oxide	0.031
Magnesium chloride	0.018
Magnesium sulfate	0.019
Hydrotrope, perfume, other minors,	0.101
10 Kathon preservative	0.0003
Water (deionized or distilled)	96.5
Target pH	6.0

* Stabilizer for hydrogen peroxide

- Preferably, to minimize the potential for dye damage as disclosed hereinabove,
- 15 H₂O₂-containing pre-spotting compositions comprise the anionic or nonionic surfactant in an amount (by weight of composition) which is less than the amount of H₂O₂. Preferably, the weight ratio of surfactant:H₂O₂ is in the range of about 1:10 to about 1:1.5, most preferably about 1:4 to about 1:3.

- 20 WHAT IS CLAIMED IS:

652050" 8-14-2009

1. A method for treating a fabric article comprising the steps of:
 - a) placing the fabric article in a container having an opening and at least one wall that defines an interior void space;
 - b) raising the temperature and relative humidity of the air within the interior void space of the container to a predetermined first temperature and a predetermined first relative humidity for a predetermined first period of time; and
 - c) changing at least one of the temperature or the relative humidity of the air within the interior void space of the container at the end of the first period of time to a predetermined second temperature and a predetermined second relative humidity for a predetermined second period of time.
2. The method according to claim 1, wherein vapor is used to raise the temperature and relative humidity of the air within the interior void space of the container.
3. The method according to claim 1, further comprising the step of allowing the temperature within the interior void space to decrease to a third temperature wherein the third temperature is less than about 45°C, preferably less than about 40°C, and more preferably less than about 35°C.
4. The method according to claim 1, wherein the container further comprises:
 - a) an active temperature controller capable of changing and maintaining the air temperature within the interior void space of the container;
 - b) a passive humidity controller capable of changing and maintaining the relative humidity of the air within the interior void space of the container;
 - c) a heating element
 - d) a vent; and
 - e) an air circulation device.
5. The method according to claim 1, wherein the vent remains open at all times.
6. The method according to claim 1, wherein vapor is introduced into the interior void space of the container comprises water and a perfume.

7. The method according to claim 4, wherein the air circulation device is a fan and the fan inlet is within the interior void space of the container so that at least a portion of the air within the void space of the container is recirculated.

8. The method according to claim 1, wherein the first temperature is at least about 45°C, preferably at least about 60°C, and most preferably at least about 70°C and the first relative humidity is at least about 20 %, preferably at least about 50%.

9. The method according to claim 1, wherein the second temperature is greater than T as defined by the equation: $T = 60 - (0.17 * RH_2)$, wherein RH_2 is the second relative humidity in percent.

10. The method according to claim 9, wherein RH_2 is at least about 85%, preferably at least about 90%.

11. The method according to claim 9, wherein the second temperature is less than about 90°C, more preferably less than about 80°C, and most preferably less than about 70°C.

12. A method for treating a fabric article comprising the steps of:

- a) placing the fabric article in a container having an opening and at least one wall that defines an interior void space;
- b) introducing ozone into the interior void space for a predetermined first period of time; and
- c) changing at least one of the temperature or the relative humidity of the air within the interior void space of the container at the end of the first period of time to a predetermined second temperature and a predetermined second humidity for a predetermined second period of time.

13. The method according to claim 12, wherein the ozone is generated by an ozone source within the interior void space of the container.

14. The method according to claim 13, wherein the ozone source is an ultraviolet lamp.

50122418-030259

15. The method according to claim 12, wherein vapor is used to change the temperature and relative humidity of the air within the interior void space of the container.

16. The method according to claim 12, further comprising a cool down step after the second period wherein the temperature within the interior void space is allowed to decrease to less than about 45°C, preferably less than about 40°C, and more preferably less than about 35°C.

17. The method according to claim 12, wherein the container further comprises:

- a) an active temperature controller capable of changing and maintaining the air temperature within the interior void space of the container;
- b) a passive humidity controller capable of changing and maintaining the relative humidity of the air within the interior void space of the container;
- c) a heating element
- d) a vent; and
- e) an air circulation device.

18. The method according to claim 17, wherein the vent remains closed at all times.

19. The method according to claim 15, wherein vapor is introduced into the interior void space of the container comprises water and a perfume.

20. The method according to claim 17, wherein the air circulation device is a fan and the fan inlet is within the interior void space of the container so that at least a portion of the air within the void space of the container is recirculated.

21. The method according to claim 12, wherein the second temperature is greater than T as defined by the equation: $T = 60 - (0.17 * RH_2)$, wherein RH_2 is the second relative humidity in percent.

22. The method according to claim 21, wherein RH_2 is at least about 85%, preferably at least about 90%.

60122418-030299

23. The method according to claim 12, wherein the second temperature is less than about 90°C, more preferably less than about 80°C, and most preferably less than about 70°C.

24. The method according to claim 1, wherein a cartridge containing a cleaning and refreshing composition is introduced into the interior void space of the container and the cleaning and refreshment composition is released from the cartridge into the interior void space of the container.

25. The method according to claim 12, wherein the container further comprises a filter.

26. The method according to claim 12, wherein a cartridge containing a cleaning and refreshing composition is introduced into the interior void space of the container and the cleaning and refreshment composition is released from the cartridge into the interior void space of the container

662020-81422109

METHOD FOR CLEANING AND REFRESHING FABRICS

ABSTRACT OF THE DISCLOSURE

A method for treating a fabric article with the following steps: placing the fabric article in a container having an opening and at least one wall that defines an interior void space. Then the temperature and relative humidity of the air within the interior void space of the container are raised to a predetermined first temperature and a predetermined first relative humidity for a predetermined first period of time. Finally, at least one of the
5 temperature or the relative humidity of the air within the interior void space of the container are changed at the end of the first period of time to a predetermined second temperature and a predetermined second relative humidity for a predetermined second period of time.

562060-8T422T09